

Coaxial Cable RG_188_A/U-60

Description

PTFE - 50 Ohm - single screen (UL AWM Style 1354)



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Strand-07	0.54 mm
Dielectric	PTFE (Polytetrafluoroethylene)		1.55 mm
Outer conductor	Copper, Silver plated	Braid, 94%	2 mm
Jacket	FEP (Fluorinated ethylene propylene)	RAL 9010 - wh	2.6 mm +/- 0.1

Print: HUBER+SUHNER RG 188 A/U-60 50 Ohm (UL logo) AWM Style 1354 (PA no.)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	3 GHz
Capacitance	97 pF/m
Velocity of signal propagation	69 %
Signal delay	4.86 ns/m
Insulation resistance	≥ 1 x 10 ⁸ MΩm
Min. screening effectiveness	≥ 41 dB (up to 1 GHz)
Max. operating voltage	≤ 1.45 kV _{rms} (at sea level)
Test voltage	1.7 kV _{rms} (50 Hz/1 min)
Voltage Rating UL	30 V

Mechanical Data

Weight	1.7 kg/100 m
Min. bending radius	static 15 mm repeated (for ≤ 50 bendings) 26 mm dynamic 39 mm

Environmental Data

Temperature range	-65 °C... +165 °C
Temperature Rating UL	80 °C
Installation temperature	-20 °C... +60 °C
Flammability 2011/65/EU (RoHS)	UL (horizontal flame test), , compliant

Additional Information

Ordering Information

Order as RG_188_A/U-60

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group U2 2 mm / 50 Ohm

Coaxial Cable RG_188_A/U-60

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.7501

b = 0.0884

f_{max} = 3

P at 1GHz = 180

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (watt) sea level 40° C ambient temperature
0.3	0.44	0.133	329
0.45	0.54	0.165	268
0.6	0.63	0.193	232
0.75	0.72	0.218	208
0.9	0.79	0.241	190
1.05	0.86	0.263	176
1.2	0.93	0.283	164
1.35	0.99	0.302	155
1.5	1.05	0.320	147
1.65	1.11	0.338	140
1.8	1.17	0.355	134
1.95	1.22	0.372	129
2.1	1.27	0.388	124
2.25	1.32	0.404	120
2.4	1.37	0.419	116
2.55	1.42	0.434	113
2.7	1.47	0.448	110
2.85	1.52	0.463	107
3.0	1.56	0.477	104